

Radiant Panel Flexible Hoses

Flexible hoses are used for connecting the mains pipework to the radiant panel and also to interconnect between two panels when they are installed in a continuous run. They are used on both the SPC Thematile TEN and Thematile TWELVE panels. The TEN panels are used for individual panels while the TWELVE panels are used on runs.

Features / Benefits

- BSRIA BG4-2004 approved
- Superior material selection to ensure longevity
- Easy to fit; reduced installation times
- Excellent abrasion and crush resistance
- Working pressure up to 10 bar at 85°C
- Number and size of hoses automatically calculated by SPC
- 3 different hoses as standard but bespoke lengths and end fittings available on request
- Quick delivery, most items ex-stock


Submittal information

- Hose – EPDM
- Braid – 304 stainless steel
- Push fit – Brass with rubber O ring and retaining collet
- Pipe ends must be deburred, cleaned and rounded before hose connector is fitted

Standard stocked hoses

| Order code | Fitting 1 | Fitting 2 | Length over fittings | Connects between |
|------------|---------------|---------------|----------------------|-------------------------|
| 70-0022 | 22mm push-fit | 22mm push-fit | 450mm | Panel to panel (TWELVE) |
| 70-0023 | 22mm push-fit | 22mm push-fit | 750mm | Mains to panel (TWELVE) |
| 70-0007 | 15mm push-fit | 10mm push-fit | 750mm | Mains to panel (TEN) |

Note: Please contact SPC for other sizes



Flexible Hose 70-0022/23



Flexible Hose 70-0007

Hose Connections

Scan the QR code below or click the link to watch our short instructional video on radiant panel hose connections:

<https://youtu.be/K2tkbn8NYwA?feature=shared>



**SCAN FOR
INSTRUCTIONAL VIDEO**



SPC House, Evington Valley Road, Leicester LE5 5LU
T: 0116 249 0044 E: spc@spc-hvac.co.uk
spc-hvac.co.uk

Ref: SPC Radiant Hoses iss4