iTwenty Eight Industrial Radiant Panels



OFFLOADING INSTRUCTIONS

OFFLOADING IS ONLY TO BE PERFORMED USING A FORKLIFT OR TELEHANDLER EQUIPPED WITH LONG-REACH WIDE FORKS, WITH A MINIMUM FORK LENGTH OF 1.5 METERS.



Inspect the Area:

- Before starting, ensure the area around the trailer is clear of obstacles and personnel
- Confirm that the ground is stable and level for safe offloading

Open the Trailer Curtains:

- Unlock and slide the curtains of the trailer open completely to provide full access to the pallets
- Ensure the area remains clear and safe for operating the machinery

Position the Forklift or Telehandler:

- Approach the trailer carefully, aligning the forklift or telehandler with the pallet to ensure a straight lift
- Make sure the forks are set at the correct width to accommodate the pallet dimensions





iTwenty Eight Industrial Radiant Panels



OFFLOADING INSTRUCTIONS

OFFLOADING IS ONLY TO BE PERFORMED USING A FORKLIFT OR TELEHANDLER EQUIPPED WITH LONG-REACH WIDE FORKS, WITH A MINIMUM FORK LENGTH OF 1.5 METERS.

Insert the Forks Fully:

- Slowly insert the forks under the pallet, ensuring they go all the way through to the other side, this helps maintain the stability of the pallet during lifting
- Check that the forks are centered and fully under the load, supporting the pallet evenly

Lift the Pallet:

- Gently lift the pallet just clear of the trailer bed, keeping the load level to prevent tipping
- Confirm that the pallet is stable on the forks before moving

Reverse the Forklift or Telehandler:

- Slowly reverse the forklift or telehandler to clear the pallet from the trailer
- Keep the load close to the ground while reversing to enhance stability and reduce the risk of tipping

Move the Pallet to Open Space:

- Once clear of the trailer, navigate to an open space designated for the pallet
- Keep the pallet low to the ground while moving and avoid sudden stops or turns

Lower and Position the Pallet:

- Carefully lower the pallet onto the ground in the desired location
- Ensure the pallet is placed evenly on the surface to avoid tipping or damage

Inspect and Final Checks:

- Perform a final check to ensure the pallet is undamaged and securely positioned



